



A126

## Cascade Jewel Take Me Anywhere Cardigan



Designed By Susie Bonell

# Jewel Take Me Anywhere Cardigan

## By Susie Bonell

Materials: Cascade Yarns Jewell Hand Dyed: 8, 9, 10 skeins of #9620

Needles: size 8 & 9

6 buttons

Gauge: 4 sts = 1", 5 rows = 1" in st st

Finished Measurements: 39" (43", 47")

8 Stitch Cable Panel (over 12 sts) Stockinette Stitch (st st)

*Pattern Note:* Some models were knit on larger needles and have a 3 sts ridge at front edges, rather than 4 as per the pattern.

Row 1, 5, 7: P2, K8, P2 Repeat.

Row 2, 4, 6, 8: (wrong side) K2, P8, K2.

Row 3: P2, C8B, P2. C8B = slip next 4 sts onto cable needle and hold in back, knit next 4 sts from L needle, knit 4 from cable needle. Repeat rows 1-8 for pat.

Lace Panel (9 stitches)

Row 1: K2, K2tog, YO, K1, YO, SSK, K2. PM = place marker

Row 2: (and all wrong side rows) Purl.

Row 3: K1, K2tog, YO, K3, YO, SSK, K1.

Row 5: K2tog, YO, K5, YO, SSK.

Row 7: K3, YO, sl 2 k-wise, K1, P2sso, YO, K3.

Row 8: Purl.

Repeat rows 1-8 for pat.

### **Back**

With size 8 needles, cast on 75, 85, 91 sts. Work in K1, P1 ribbing for 2 ½" increasing to 85, 93, 101 sts on last wrong side row. Change to larger needles and establish pattern as follows: K5 (K9, K13) st st PM, Row 1 cable panel (12 sts), PM, Row 1 Lace Panel (9 sts), PM, Row 1 cable panel (12sts), PM, Row 1 Lace Panel (9 sts), PM, Row 1 Cable Panel (12 sts), PM, Row 1 Lace Panel (9 sts), PM, Row 1 Cable Panel (12 sts), K5( K9, K13) st st. Continue working as established until back measures 15 ½", 16", 16 ½" or desired length to underarm.

### **Armhole Shaping**

Bind off 6 (8, 8) sts at the beg of the next two rows. Continuing in patterns, dec 1 st each side every other row 5( 7, 7 )times. Work until armhole measures 9 ½", 10", 10 ½".

Shoulders

Bind off 5 (5, 6) sts on next 4 rows. Bind off 6 (6, 7) sts next 2 rows. Bind off remaining.

### **Right Front**

With size 8 needles, cast on 38 (43, 45) sts. Work in K1, P1 ribbing for 2 ½" increasing to 43, (47, 51) sts on last wrong side row. Change to larger needles and establish pattern as follow: K5 (9, 13) st st, PM, Row 1 of Cable Panel (12 sts), PM, Row 1 of Lace Panel (9 sts), PM, Row 1 of Cable Panel (12 sts), PM, K5 ( K5, K5) st st. Work as established to armhole as for back, Work armhole shaping as for back at armhole edge. Continuing in pattern work until armhole meas-

ures 6 ½" (all sizes) and at NECK EDGE bind off 8 (9, 9) sts, then dec 1 st every other row 7 (7, 8) times. Continue until front measures same as back to shoulders and work shoulder shaping as for back.

Repeat for Left front reversing shaping.

### **Sleeves**

With size 8 needles, cast on 36 (38, 41) sts. Work in K1, P1 ribbing for 2 ½" increasing to 41, (43,47) on last wrong side row. Change to larger needles and establish patterns as follows: K4 (5, 7) st st ,PM, Row 1 of Cable Panel (12 sts), PM, Row 1 of Lace Panel (9 sts), PM, Row 1 of Cable Panel (12 sts), K4 ( K5, K7) st st. Work patterns as established while working the increases in st st as follows: Inc 1 st each side every 4th row 17( 13, 18) times, then every 6th row 1, 4, 1 times. Work until sleeves measures 17 ½" (18 ½", 18 ½") or desired length to armhole.

### **Cap Shaping**

Bind off 6 (8, 8) sts on next 2 rows. Dec 1 st each side every other row 5 ( 7, 7) times. Dec 1 st every row 8, 1, 7 times. Dec 1 st every 2nd row 7, 9, 7 times. Bind off 3 sts at the beg of next 4 rows. Bind off remaining.

Work 2nd sleeve the same.

Steam and shape pieces as necessary. Sew shoulder seams.

**Neck Trim:** With smaller needles and right side facing you, pick up and knit 8 (9, 9) bound off sts, 11 ( 13, 14) sts from side neck 30( 32, 34) sts from back 11( 13, 14) from other side neck, 8(9, 9) from bound off sts. Work in K1, P1 ribbing for 6 rows. Bind off in pattern.

**Left Front Trim:** With smaller needles and right side facing you pick and knit 98 (100, 102) sts and work in K1, P1 ribbing for 6 rows and bind off in pattern. Mark placement for 6 buttons.

**Right Front Trim:** Work as for Left Front working buttonholes corresponding to markings on rows 3 and 4 of trim as follows: On row 3: bind off 2 sts, on row 4 cast on 2 sts above bound off sts to complete buttonhole.

Sew in sleeves. Sew side seams. Weave in all ends. Steam again if necessary.