



W433

Sitka
Women's Cardigan



Designed by Marelle Hurter

Sitka Women's Cardigan
Designed by Marelle Hurter

MATERIALS: SITKA (100g skeins)

9(10; 10; 11) skeins of SITKA Col. 21; 3 buttons.

One pair US Needle size 9 (5.5mm)

MEASUREMENTS:

Original garment worked in size 36" (92cm)

To fit Bust: 36 (38, 40, 42)"

Actual all round measurement of garment: Bust: 39 (41, 43, 45) "

Length to shoulder: 27 (28; 29; 30)"

Sleeve seam: 15 (16;16;17)"

THE INSTRUCTIONS ARE GIVEN FOR THE SMALLEST SIZE, WITH THE LARGER SIZES IN BRACKETS; WHERE ONLY ONE FIGURE IS GIVEN, IT APPLIES TO ALL SIZES.

TENSION: SAVE TIME, TAKE TIME, CHECK TENSION.

21sts and 20 rows = 3"(10cm) over Eyelet Mock Rib patt using US Needle size 9 (5.5mm)

16sts and 22 rows = 3"(10cm) over stocking stitch using US Needle size 9 (5.5mm)

FOR BEST RESULTS IT IS ESSENTIAL TO OBTAIN THE CORRECT TENSION.

IF THERE ARE TOO FEW STS ON TEST SWATCH, USE THINNER NEEDLES;

IF THERE ARE TOO MANY STS, USE THICKER NEEDLES.

ABBREVIATIONS:

alt = alternate; **beg** = begin(ning); **cont** = continue; **dec** = decrease; **folll(s)** = follow(s)ing; **inc(s)** = increase(s); **k** = knit; **pssso** = pass slipped stitch over; **patt(s)** = pattern(s); **p** = purl; **rem** = remain(ing); **rep** = repeat; **rev** = reverse; **R(W)S** = right(wrong) side; **R(W)SF** = right(wrong) side facing; **R(W)SR** = right(wrong) side row; **sl** = slip; **st(s)** = stitch(es); **st st** = stocking stitch; **tog** = together; **yrn** = yarn round needle.

STICHES USED:

EYELET MOCK CABLE RIB PATTERN (Multiple of 5sts + 2):

1st row: RSF, p2, *sl 1, k2, pssso, p2, rep from * to end.

2nd row: K2, *p1, yrn, p1, k2, rep from * to end.

3rd row: P2, *k3, p2, rep from * to end.

4th row: K2, *p3, k2, rep from * to end.

Rep these 4 rows.

STOCKING STITCH:

1st row: RSF, K.

2nd row: WSF, P.

Rep these 2 rows.

BACK:

Cast on 107(112;117;122)sts and cont straight in Eyelet Mock Cable Rib patt (SEE STS USED) until work measures 5 (5.5; 6 ;6)” from beg ending with a WSR.

Next row, dec row: P one row on RS, dec 27 (28; 29; 30)sts evenly across row = 80(84;88;92)sts.

Next row: P (= ridge line). RSF, now cont straight in st st, beg with a k row, and when work measures 19(19; 20; 20.5)” from beg ending with a WSR

SHAPE ARMHOLES: Cast off 4sts at beg of next 2 rows, 3sts at beg of foll 2 rows, 2sts at beg of foll 2(2; 4; 4) rows, then dec 1 st (= work 2tog) at each end of every foll alt row 1(2; 2; 2) times = 60(62; 62; 66)sts. Cont straight and when work measures 27 (27; 29; 30)” from beg ending with a WSR

SHAPE SHOULDERS: Cast off 6sts at beg of next 4 rows, then cast off 6(6; 6; 7)sts at beg of foll 2 rows = 24 (26;26;28)sts. Cast off rem sts for neck opening

RIGHT FRONT:

Cast on 52(57; 57; 62)sts and cont straight in Eyelet Mock Cable Rib patt until work measures 5(5.5; 6; 6)” from beg ending with a WSR

Next row, dec row: P one row on RS, dec 12(15; 13; 16)sts evenly across row = 40(42; 44; 46)sts.

Next row: P. RSF, now cont straight in st st, beg with a k row, until work measures 12.5(13; 13; 14)” from beg ending with a WSR

Next row, buttonhole row: K3sts, cast off 3sts, k to end of row.

Next row: P, casting on 3sts over buttonhole. Cont straight until work measures 40(41; 42; 44)cm from beg ending with a WSR.

Next row, buttonhole row: K3sts, cast off 3sts, k to end of row.

Next row: P, casting on 3sts over buttonhole. Cont straight and when work measures 16(18.5;19;20)'' from beg ending with a WSR

SHAPE V-NECK: Dec 1 st (= work 2tog) at beg (neck edge) of next and at same edge of every foll alt row 16 (18;17;19) times in all, then every foll 4th row 4(3;4;3) times.

AT THE SAME TIME when work measures 19(19; 20; 20)'' from beg ending with a RSR

SHAPE ARMHOLE: Bind off 4sts at beg of next row, 3sts at beg of foll alt row, 2sts at beg of foll alt row 1(1; 2; 2) times, then dec 1 st at beg of every foll alt row 1(2; 2; 2) times. When all shapings are complete = 10(10; 10; 11)sts. Cont straight and when work measures 28(28; 29; 30)'' from beg ending with a RSR

SHAPE SHOULDER: Bind off 6sts at beg of next row = 4(4; 4; 5)sts. Work one row, then Bind off rem sts.

LEFT FRONT:

Work as for right front, rev shapings and omitting buttonholes.

SLEEVES (Both Alike):

Cast on 57(57; 57; 62)sts and work in Eyelet Mock Cable Rib patt (SEE STS USED) for 4''(10cm) ending with a RSR.

Next row, dec row: Work one row on WS, dec 15(13; 13; 14)sts evenly across row = 42(44; 44; 48)sts

Next 2 rows: P. Now cont in st st (beg with a k row), inc 1 st at each end of next and every foll 6(6; 4; 4)th row 6(5; 2; 1) times in all, then every foll 8(8; 6; 6)th row 3(4; 9; 10) times = 60(62; 66; 70)sts. Cont straight and when work measures 15(16; 16; 16.5)'' from beg ending with a WSR

SHAPE TOP OF SLEEVE: Cast off 3(4; 4; 4)sts at beg of next 2 rows, 2sts at beg of next 8(8; 10; 10) rows, then dec 1 st (= work 2tog) at each end of every foll alt row 7(8; 9; 8) times, then cast off 2sts at beg of next 6 rows = 12(14; 14; 14)sts. Cast off rem sts.

TO MAKE UP:

RIGHT FRONT BAND: RSF, using US Needle size 9(5.5mm) , pick up and k42(42; 47; 47)sts evenly along slope of right front and knit one row, then work in Eyelet Mock Cable Rib patt for 2,5cm ending with a WSR.

Next row, buttonhole row: Work 3sts, cast off 3sts, work to end of row.

Next row: Work in patt, casting on 3sts over buttonhole. Cont straight until work measures 5cm from beg ending with a WSR, cast off all sts.

LEFT FRONT BAND: Work as for right front band, omitting buttonhole. Sew shoulder seams.

FRONT AND BACK TRIMS: RSF, pick up and k74(75; 76; 80)sts evenly along straight edge of right front, 32 (32; 34; 34)sts evenly along shaped edge of front neck, 26(28; 28; 30)sts across back neck, 32(32; 34; 34)sts down shaped edge of left front = 238(242; 248; 258)sts.

Next row: K. Bind off all sts. Set in sleeves. Sew up side and sleeve seams. Sew on buttons.

